

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-026829

(43)Date of publication of application : 25.01.2000

(51)Int.Cl.

C09J163/00

C08G 59/40

C09J 9/02

(21)Application number : 10-193821

(71)Applicant : THREE BOND CO LTD

(22)Date of filing : 09.07.1998

(72)Inventor : OSADA MASAYUKI  
TOMIOKA HIDEKAZU

## (54) THERMOSETTING ELECTROCONDUCTIVE ADHESIVE

## (57)Abstract:

PROBLEM TO BE SOLVED: To obtain a thermosetting electroconductive adhesive improved in storage stability, which adhesive contains a product prepared by subjecting to a specified pretreatment a curing agent prepared by pretreating with an isocyanate the reaction product of an imidazole derivative with an epoxy compound.

SOLUTION: There is provided a thermosetting electroconductive adhesive comprising a curing agent prepared by pretreating with an isocyanate the reaction product of an imidazole derivative with an epoxy compound, an epoxy composition curable with the curing agent, and an electroconductive material, wherein the curing agent is further treated with an isocyanate compound and a polyol compound in an epoxy resin which does not dissolve or swell the curing agent. In an embodiment, the pretreatment with the isocyanate compound and the polyol compound is carried out by using 100 pts.wt. curing agent, 0.01-20 pts.wt. isocyanate compound, and 0.01-20 pts.wt. polyol compound.

10/511172

DT04 Rec'd PCT/PTO 13 OCT 2004

isocyanato compound and a polyol compound in an epoxy resin not dissolving or swelling the curative.

USE - The thermosetting electroconductive adhesives are for adhering counter wiring patterns by thermal contact bonding on electronic parts assembly.

ADVANTAGE - The thermosetting electroconductive adhesives have much improved storage stability, excellent solvent resistance and thermal and physical stability without foam mixing and fall in glass transition temperature even with use of a polyol compound.

Dwg.0/1

Title Terms: THERMOSETTING; ELECTROCONDUCTING; ADHESIVE; IMPROVE; STORAGE; STABILISED; COMPRISE; CURE; OBTAIN; TREAT; REACT; PRODUCT; IMIDAZOLE; DERIVATIVE; EPOXY; COMPOUND; ISOCYANATE

Derwent Class: A21; A25; A81; G03; L03

International Patent Class (Main): C09J-009/02; C09J-163/00

International Patent Class (Additional): C08G-059/40; C09J-175/00

File Segment: CPI

10/511172

DT04 Rec'd PCT/PTO 13 OCT 2004

File 351:Derwent WPI 1963-2004/UD,UM &amp;UP=200463

(c) 2004 Thomson Derwent

\*File 351: For more current information, include File 331 in your search.  
Enter HELP NEWS 331 for details.

1/5/1

DIALOG(R)File 351:Derwent WPI

(c) 2004 Thomson Derwent. All rts. reserv.

013005363

WPI Acc No: 2000-177215/200016

XRAM Acc No: C00-055606

Thermosetting electroconductive adhesives with improved storage stability  
- comprising a curative obtained by treating a reaction product of an  
imidazole derivative and an epoxy compound with an isocyanate

Patent Assignee: TOKYO THREE BOND CO LTD (TOKT )

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2000026829	A	20000125	JP 98193821	A	19980709	200016 B
JP 3562323	B2	20040908	JP 98193821	A	19980709	200459

Priority Applications (No Type Date): JP 98193821 A 19980709

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 2000026829	A		6	C09J-163/00	
JP 3562323	B2	10		C09J-009/02	Previous Publ. patent JP 2000026829

Abstract (Basic): JP 2000026829 A

NOVELTY - A thermosetting electroconductive adhesive comprises a  
curative obtained by treating a reaction product of an imidazole  
derivative and an epoxy compound with an isocyanate, an epoxy  
composition to be cured with the curative and an electroconductive  
material.

DETAILED DESCRIPTION - The curative is further treated with an  
isocyanato compound and a polyol compound in an epoxy resin not  
dissolving or swelling the curative.

USE - The thermosetting electroconductive adhesives are for  
adhering countering wiring patterns by thermal contact bonding on  
electronic parts assembly.

ADVANTAGE - The thermosetting electroconductive adhesives have much  
improved storage stability, excellent solvent resistance and thermal  
and physical stability without foam mixing and fall in glass transition  
temperature even with use of a polyol compound.

Dwg.0/1

JP 2000026829 A

NOVELTY - A thermosetting electroconductive adhesive comprises a  
curative obtained by treating a reaction product of an imidazole  
derivative and an epoxy compound with an isocyanate, an epoxy  
composition to be cured with the curative and an electroconductive  
material.

DETAILED DESCRIPTION - The curative is further treated with an